

Chill and Freezer Rooms

POLYURETHANE INSULATED PANELS

- Formed from high density (40kg/sq.m) polyurethane foam
- Clad in food safe white PVC coated galvanised steel
- Polyurethane foam conforms to fire safety standard BS4735
- Corrosion resistant locks and receivers
- Tongued and grooved edges
- Internal corners are finished with PVC coving
- CFC free

SIZE OPTIONS

Panel Thickness Temperature

80mm 0°C to 60°C

100mm -30°C to 60°C

- Modular construction based on 100 mm increments creates purpose built rooms of varying sizes
- Standard heights of 2.0m and 2.2m
- Other heights of up to 10m available on request

FLOORS

- Standard floor 80mm or 100mm polyurethane panels coated in 2mm non-slip PVC coated material
- A reinforced floor with 2mm galvanised treadplate and 10mm marine plywood is available for heavier loads such as pallet trucks

INSULATED DOORS

- Doors can be supplied either hinged or sliding
Standard ope sizes are:
0.8m x 1.89m
1.4m x 1.89m
- Off standard sizes can be made to order
- In low temperature applications the door surround is fitted with a low voltage heater element to prevent the door freezing shut
- Doors include locks, which are supplied with keys and are fitted with an internal release mechanism for added safety

