

Model

eikon[™] e4



e4-1430 **Standard Features** Merrychef m 0 80 cooking methods while in microwave mode Cool to touch door exterior

- Advanced Cooking Technology[®] combines three heat technologies of convection, impingement, and microwave for fast even heating of food product
- Up to fifteen (15) times faster than conventional
- "Ventless* Cooking" capability through standard built-in catalytic converter with full protein capability
- Ability to use a standard, ¼ size metal baking pan
- Automatic voltage detection (U.S. only)
- MenuConnect[™] software capability

*Local codes prevail. These are the "authority having jurisdiction" as stated by the National Fire Protection Association, Inc., in NFPA96-1994.


Specifications

Construction

- 430 stainless steel casework and 304 stainless steel interior cavity
- Easy side panel access to internal components
- Easily accessible, front facing air filter

EasyToUCH[™] Control Panel

- Icon driven, color touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power settings and user instructions for each stage
- Self diagnostics capability to monitor components
- Easy menu updates or data transfer via USB memory stick •
- Multi-languages available •



The convection fan pulls air in through the grease filter (1) which removes the majority of particulates from the air flow. The air is then heated and returned to the cavity through the catalysts (2) and impinger plates (3) to produce an even heat pattern in the oven. This heat layout minimizes the areas where grease can build up, allowing food to cook evenly to produce a crisp golden finish.

Merrychef U.S.A. 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 877-404-6872 Fax: 800.285-9511 www.merrychefusa.com



Ð

NSF



○Merrychef

2 units


1 unit


-	<u> </u>
7	
-	כ
	TM
(D
-	

 \square

Overall Size			Specifications	
Height	23.3"	591 mm	Preheat Time	15 minutes
Width	23"	584 mm Control System	easyToUCH [™] , iconic symbo	
Depth (overall without handle)	25.3"	643 mm		touch screen control pane
Depth (door open 90 degrees)	39.3"	999 mm	Cooking Stages	6
Weight	182 lbs	82.5 kg	Total Cooking Programs	1,024
Shipping Weight	210 lbs	95.4 kg	Maximum Cooking Time	60:00 (10:00 x6 Stages)
Shipping Box Size	37.4 x 30.3 x 33.85"	950 x 770 x 860mm	Defrost	No
Oven Cavity Dimensions			Microwave Distribution System	Rotating Active Antenna
Height	8.6"	218 mm	Magnetron(s)	2
Width	14.8"	375 mm	Display	Touchscreen
Depth	12.3"	312 mm	Interior Light	No
Volume	0.90 ft ³ (Cu. Foot)	25.5 liters	Automatic Voltage Sennsor	Yes
Wall Clearance			USB & MenuConnect Software	Yes
Тор	2″	50.8 mm	Temperature Range	Off, 212°F - 527°F
Sides	2"	50.8 mm	Temperature Increments	1°F (from 212°F upwards)
Electrical Specifications			Air Filter	Yes - removable
Phase	1ph		Convection Fan Speed	10%-100%
Dual Voltage	208 / 240		Convection Fan Speed Increments	1%
Frequency	60Hz		Microwave Power	0%(off), 5%-100%
Amperage Requirement	30 amp		Microwave Power Increments	1% (from 5% upwards)
Plug	NEMA 6-30P	G e	Rack	Yes - 1
Cord Length	6 ft		Rack Positions	2
Power Consumption	6200W	NEMA 6-30P	Turntable	No
Power Output (Microwave)	1500W		Stackable	Yes Kits and stacking cart availabl
Power Output (Convection)	3.2kW		Warranty	1 year parts and labor
		1	Accessories in Box	
			Chemco Dirt Buster III Cleaner	1 unit
			Chemco Oven Shield	1 unit

Model e4-1430





For further information on Merrychef products and service or advice on which machine suits you best please contact your sales representative or visit our website at www.merrychefusa.com.

Spray Triggers

Operator Manual / Cleaning Instructions

Specifications subject to change without notice.

Merrychef U.S.A. 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 877-404-6872 Fax: 800.285-9511

www.merrychefusa.com



