



ECO-FRIENDLY  
REFRIGERANT R290



## MD1902X

Stainless Steel Multideck

### Product features:

- Premium design
- Stainless steel exterior and interior
- Temperature Class 3M1
- Adjustable shelves with tilting function
- Shelf stopper for tilting is accessory
- LED interior light with switch
- Digital controller and temperature display
- Night blind / Curtain with soft release



Soft release night  
blind / curtain



Adjustable shelves  
with tilting function

### Open front multideck with stainless steel interior and exterior

The TEFCOLD MD-X range of open front multidecks finished in stainless is a great choice for shops, cafes, sandwich shops, butchers and convenience stores. Available in different widths between 685mm and 1885mm there is a size to suit most situations.

The unit is only 680mm deep and is ideal where there is limited floor space but you need to maximise refrigerated display area. With a base shelf and 4 adjustable shelves there is plenty of product storage space. Mirror finish stainless steel interior helps give a sense of space within the cabinet while bright white vertical LED lighting gives excellent illumination of the product (the MD1902X also has a horizontal LED light across the top).

The temperature range can be adjusted to suit your requirement including fresh meat, dairy or soft drinks or beer. Shelves can be angled between 2 and 20 degrees to give extra merchandising options (front shelf stops are required if shelves are angled). The unit comes fitted with rollers to enable the unit to be moved for cleaning, there is also an option for castors. The unit is also available in black.

Design and Material	
Shelves No & Type	4 SS304 shelves, tilting
Shelf Color	Stainless steel
Feet / Legs	2 adjustable feet
Castors	4 rollers
Exterior Finish	Stainless steel
Interior Finish	Stainless Steel
Interior Light	LED

Measures and Content		
Temperature Range	°C	-1 to +5
Climate Class		3
Gross / Net Weight	kg	272 / 243
Gross / Net Volume	l	1314 / 954
Total Display Area	m <sup>2</sup>	2,3

Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R2
Refrigerant Charge	g	2x 105
GWP		3

Power and Consumption		
Energy Class	A-G	E
Energy Consumption	kWh/24h	25
Annual Energy Consumption	kWh/year	9125
EEL		62,8
Input Power	W	1250
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	55

Dimensions		
Internal Dimension (WxDxH)	m	1800 x 560 x 1355
External Dimension (WxDxH)	m	1885 x 680 x 1985
Packed Dimension (WxDxH)	m	1970 x 750 x 2140

