



PDC125-P

Refrigerated Showcase



ECO-FRIENDLY
REFRIGERANT R290

Product features:

- Open top for easy access to products
- Sliding lids are optional
- Glass sides for better presentation of products
- Impressive storage space
- Tilting function for better product display
- Optimized airflow for stable temperature
- Strong wheels for mobility
- Stainless steel bumper bars



Sliding glass lids as option



Strong castors

| Measures & Content | | |
|--------------------|----|-----------|
| Temperature Range | °C | -1 to 5 |
| Climate Class | | 3 |
| Gross / Net Weight | kg | 169 / 130 |
| Gross / Net Volume | l | 270 / 235 |

Black impulse cooler (island cooler)

Large sized black impulse cooler ideal as island cooler.

Product visibility is great - all sides are glass - plus it has a high loading line compared to many other similar units. Glass lids are optional for the large PDC125-I - not for the medium unit.

The PDC range is great for supermarkets, gas stations, convenience stores and cafeterias for e.g berries, fruit, vegetables, sandwiches or other take away. It has stainless steel bumper bars as standard for protection and easy handling of the cooling unit. Moving it around on the solid castors is easy, so it can easily be moved to a different location in the store.

The design is also optimized for two units to be placed next to each other in a line, if needed.

If on the other hand the unit is placed up against a wall or at the end of an aisle, then PDC125-I has a tilting function to an 11 degree angle for better product display.

Cooling is ventilated. Guided airflow makes an even distribution of the cooling effect.

| Design, Materials & Cooling | | |
|-----------------------------|---------|-------------------------|
| Lid Number & Type | | |
| Castors | | 4 castors |
| Exterior Finish | | Plastified coated steel |
| Interior Finish | | Stainless steel |
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 150 |
| Noise Level | db(A) | 51 |
| Input Power | W | 1178 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Energy Consumption | kWh/24h | 11,96 |
| Thermometer | | Yes |
| Internal Dimension (WxDxH) | mm | 1210 x 905 x 220 |
| External Dimension (WxDxH) | mm | 1250 x 1203 x 971 |
| Packed Dimension (WxDxH) | mm | 1370 x 1190 x 1080 |
| 40ft Container Load | pcs | 20 |